

FloMag[®] PWT (Potable Water Treatment)

Magnesium Oxide

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Date of issue: 04/18/2014

Revision date: 04/09/2021

Supersedes: 07/08/2019

Version: 1.3

SECTION 1: Identification

1.1. Identification

Product form : Substance
Trade name : FloMag[®] PWT 12 x 40
FloMag[®] PWT 6 x 16
FloMag[®] PWT Prilled 30
Chemical name : Magnesium oxide
CAS-No. : 1309-48-4
Formula : MgO
Other means of identification : calcined brucite magnesia, calcined magnesia, calcined magnesite, magnesite burnt deadburned refractory, periclase, sea-water magnesia, oxomagnesia

1.2. Recommended use and restrictions on use

Use of the substance/mixture : For use in potable water treatment (NSF Standard 60 for Drinking Water Chemicals).

1.3. Supplier

Martin Marietta Magnesia Specialties
1800 Eastlake Road
Manistee, Michigan 49660 - USA
T +001 410 780 5500

1.4. Emergency telephone number

Emergency number : CHEMTREC, U.S.: 1-800-424-9300 INTERNATIONAL: +1-703-527-3887 Available 24/7

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS US classification

Not classified

2.2. GHS Label elements, including precautionary statements

GHS US labeling

No labeling applicable

2.3. Other hazards which do not result in classification

Other hazards not contributing to the classification : No additional hazards have been identified.

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substances

Substance type : Mono-constituent
Name : FloMag[®] PWT (Potable Water Treatment) Magnesium Oxide
CAS-No. : 1309-48-4

Name	Product identifier	%	GHS US classification
Magnesium oxide	(CAS-No.) 1309-48-4	98	Not classified
Oxides of silicon, iron, aluminum, and calcium	(CAS-No.) mixture	2	Not classified

3.2. Mixtures

Not applicable

FloMag[®] PWT (Potable Water Treatment) Magnesium Oxide

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 4: First-aid measures

4.1. Description of first aid measures

- First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
- First-aid measures after inhalation : If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing.
- First-aid measures after skin contact : Not expected to be an irritant. Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse.
- First-aid measures after eye contact : Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or redness persists.
- First-aid measures after ingestion : Rinse mouth. Do NOT induce vomiting.

4.2. Most important symptoms and effects (acute and delayed)

- Symptoms/effects : Not expected to present a significant hazard under anticipated conditions of normal use. Do not breathe dust.
- Symptoms/effects after inhalation : Inhalation may cause: irritation, cough, shortness of breath.
- Symptoms/effects after skin contact : None under normal conditions.
- Symptoms/effects after eye contact : May cause eye irritation.
- Symptoms/effects after ingestion : Ingestion generally causes purging of the bowels. Swallowing large amounts may cause bowel obstruction.

4.3. Immediate medical attention and special treatment, if necessary

No special procedures required.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

- Suitable extinguishing media : Not combustible. If there is a fire close by, use suitable extinguishing agents. Water fog. Carbon dioxide. Dry powder. Foam.
- Unsuitable extinguishing media : None known.

5.2. Specific hazards arising from the chemical

- Fire hazard : If heated to decomposition (>1700 °C), magnesium oxide fumes may be generated.
- Explosion hazard : Product is not explosive.
- Reactivity : Reacts with : Incompatible materials.

5.3. Special protective equipment and precautions for fire-fighters

- Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Do not allow run-off from fire fighting to enter drains or water courses.
- Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.
- Other information : No additional risk management measures required.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Avoid creating or spreading dust. Dust deposited may be vacuum cleaned.

6.1.1. For non-emergency personnel

- Protective equipment : Where excessive dust may result, use approved respiratory protection equipment.
- Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

- Protective equipment : Where excessive dust may result, use approved respiratory protection equipment.
- Emergency procedures : Sweep spilled substance into containers; if appropriate, moisten first to prevent dusting.

6.2. Environmental precautions

Prevent entry to sewers and public waters.

6.3. Methods and material for containment and cleaning up

- For containment : Contain and collect as any solid.
- Methods for cleaning up : Sweep up spilled material without making dust.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

FloMag® PWT (Potable Water Treatment) Magnesium Oxide

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Provide good ventilation in process area to prevent formation of dust.
Hygiene measures : Handle in accordance with good industrial hygiene and safety procedures.

7.2. Conditions for safe storage, including any incompatibilities

- Storage conditions : Keep container closed when not in use.
Incompatible materials : ACID (Strong) - vigorous reaction, heat generated; Chlorine Trifluoride reacts violently, producing flame; Phosphorous Pentachloride - incandesces brilliantly. NOTE: Exposure to water may cause this product to slowly hydrate, during which heat may be generated (exothermic reaction).
Prohibitions on mixed storage : Keep away from incompatible materials.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

FloMag® PWT 12 x 40 FloMag® PWT 6 x 16 FloMag® PWT Prilled 30 (1309-48-4)		
ACGIH	Local name	Magnesium oxide
ACGIH	ACGIH TWA (mg/m³)	10 mg/m³
Magnesium oxide (1309-48-4)		
ACGIH	Local name	Magnesium oxide
ACGIH	ACGIH TWA (mg/m³)	10 mg/m³
ACGIH	Remark (ACGIH)	(inhalable fraction)
ACGIH	Regulatory reference	ACGIH 2019
OSHA	OSHA PEL (TWA) (mg/m³)	15 mg/m³
Oxides of silicon, iron, aluminum, and calcium (mixture)		
Not applicable		

8.2. Appropriate engineering controls

- Appropriate engineering controls : Provide local exhaust or general room ventilation to minimize exposure to dust. Avoid dispersal of dust in the air (i.e. clearing dust surfaces with compressed air).

8.3. Individual protection measures/Personal protective equipment

Eye protection:

Safety glasses with side guards should be worn to prevent injury from airborne particles and/or other eye contact with this product. Where excessive dust may result, wear goggles

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment. Use an N95 respirator.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

- Physical state : Solid
Appearance : Powder.
Color : white
Odor : odorless
Odor threshold : No data available
pH : No data available
pH solution : 10.3 saturated aqueous solution
Melting point : 2827 (2797 - 2857) °C
Freezing point : No data available
Boiling point : 3600 °C
Flash point : Product does not sustain combustion

FloMag® PWT (Potable Water Treatment) Magnesium Oxide

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: Non flammable.
Vapor pressure	: No data available
Vapor pressure at 50 °C	: 0 hPa
Relative vapor density at 20 °C	: 0
Relative density	: No data available
Specific gravity / density	: 3.58 g/cm ³ (theoretical density of MgO)
Molecular mass	: 40.3 g/mol
Solubility	: In water, material is partially soluble.
Log Pow	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: > 1700 °C
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosion limits	: No data available
Explosive properties	: Product is not explosive.
Oxidizing properties	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Reacts with : Incompatible materials.

10.2. Chemical stability

Stable at ambient temperature and under normal conditions of use.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Keep/Store away from incompatible materials.

10.5. Incompatible materials

ACID (Strong) - vigorous reaction, heat generated; Chlorine Trifluoride reacts violently, producing flame; Phosphorous Pentachloride - incandesces brilliantly. NOTE: Exposure to water may cause this product to slowly hydrate, during which heat may be generated (exothermic reaction).

10.6. Hazardous decomposition products

If magnesium oxide is heated to the point of volatilization (i.e, >1700 C), magnesium oxide fumes may be generated.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified (Based on available data, the classification criteria are not met)
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

ATE US (oral)	3990 mg/kg body weight
Magnesium oxide (1309-48-4)	
LD50 oral rat	3870 - 3990 mg/kg
ATE US (oral)	3870 mg/kg body weight

Skin corrosion/irritation	: Not classified (Based on available data, the classification criteria are not met)
Serious eye damage/irritation	: Not classified (Based on available data, the classification criteria are not met)
Respiratory or skin sensitization	: Not classified (Based on available data, the classification criteria are not met)
Germ cell mutagenicity	: Not classified (Based on available data, the classification criteria are not met)
Carcinogenicity	: Not classified (Based on available data, the classification criteria are not met)
Reproductive toxicity	: Not classified (Based on available data, the classification criteria are not met)
Specific target organ toxicity – single exposure	: Not classified (Based on available data, the classification criteria are not met)

FloMag® PWT (Potable Water Treatment) Magnesium Oxide

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Specific target organ toxicity – repeated exposure	: Not classified (Based on available data, the classification criteria are not met)
Aspiration hazard	: Not classified (Based on available data, the classification criteria are not met)
Viscosity, kinematic	: No data available
Likely routes of exposure	: Dermal. Inhalation.
Symptoms/effects	: Not expected to present a significant hazard under anticipated conditions of normal use. Do not breathe dust.
Symptoms/effects after inhalation	: Inhalation may cause: irritation, cough, shortness of breath.
Symptoms/effects after skin contact	: None under normal conditions.
Symptoms/effects after eye contact	: May cause eye irritation.
Symptoms/effects after ingestion	: Ingestion generally causes purging of the bowels. Swallowing large amounts may cause bowel obstruction.

SECTION 12: Ecological information

12.1. Toxicity

Magnesium oxide (1309-48-4)

LC50 fish 1	1355 mg/l
EC50 Daphnia 1	190 mg/l

12.2. Persistence and degradability

FloMag® PWT 12 x 40 FloMag® PWT 6 x 16 FloMag® PWT Prilled 30 (1309-48-4)

Persistence and degradability	Not established.
-------------------------------	------------------

12.3. Bioaccumulative potential

FloMag® PWT 12 x 40 FloMag® PWT 6 x 16 FloMag® PWT Prilled 30 (1309-48-4)

Bioaccumulative potential	Not established.
---------------------------	------------------

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Other information : Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Disposal methods

Waste disposal recommendations	: Dispose in a safe manner in accordance with local/national regulations.
Ecology - waste materials	: Avoid release to the environment.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Not regulated.

Transport by sea

Not regulated.

Air transport

Not regulated.

SECTION 15: Regulatory information

15.1. US Federal regulations

FloMag® PWT (Potable Water Treatment) Magnesium Oxide

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Magnesium oxide (1309-48-4)		
Listed on the United States TSCA (Toxic Substances Control Act) inventory		
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard	No
	Delayed (chronic) health hazard	No
	Fire hazard	No
	Sudden release of pressure hazard	No
	Reactive hazard	No
SARA Section 313 - Emission Reporting	Magnesium oxide is not hazardous and is not subject to Form R reporting requirements.	

15.2. International regulations

Magnesium oxide (1309-48-4)		
Jurisdiction	List	Comment
Asia Pacific	Asia - PAC	
Australia	Australian Inventory of Chemical Substances (AICS)	
	National Pollutant Inventory	magnesium oxide fume
	Priority Existing Chemicals	
China	Inventory of Existing Chemical Substances (IECSC)	
Japan	Existing and New Chemical Substances (ENCS)	# 1-465; inorganic compounds
Korea	KECI (Chemical Inventory of Korea)	KE-22728
New Zealand	Inventory of Chemicals (NZIoC)	HSNO approval
Phillippines	Inventory of Chemicals and Chemical Substances (PICCS)	
Europe	EEC International Cosmetics Ingredients Inventory (INCI)	absorbant/ buffering/ opacifying / additives
	EU REACH pre-registered	
	EU Inventory of Existing Commercial Chemical Substances (EINECS)	215-171-9
	German Water Hazard Class Substance List	5208 Classification: VwVwS
	Switzerland Giftliste 1 (List of Toxic Substances)	G-2368
Canada	Canadian Domesticated Substances List (DSL)	
	WHMIS Ingredient List	
United States	ACGIH Threshold Limit Values (TLV)	
	EPA Pesticide Inert Ingredients	
	FDA Priority-based Assessment of Food Additives (PAFA)	
	FDA Regulations	Use as colorant.
	High Production Volume Chemicals (HPV)	
	National Toxicology Program Technical Reports List	
	NIOSH Hazard, Toxicology, and Use Information	
	NIOSH Health Hazards	
	NIOSH Recommended Exposure Limits	10 mg/m ³
	OSHA Permissible Exposure Limits	8 hour TWA: total particulates 15 mg/ m ³
	Toxic Substances Control Act (TSCA) Inventory	
	Toxic Inventory Update Rule	
TSCA Section 8A-Preliminary Assessment Information Rule (PAIR)		
Other	Health Hazards	RTECS: OM3850000
	High Production Volume Chemicals: ICCA	
	High Production Volume Chemicals: OECD	

15.3. US State regulations

⚠️ WARNIN : This product can expose you to Lead and Nickel compounds, which are known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

FloMag® PWT (Potable Water Treatment) Magnesium Oxide

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Component	State or local regulations
Magnesium oxide(1309-48-4)	U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List

SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date : 04/09/2021

Data sources : ACGIH 2000.

Chemical Inspection & Regulation Service; accessed at: http://www.cirs-reach.com/Inventory/Global_Chemical_Inventories.html.

Ind. Exposure & Control Techn. for OSHA Regulated Substances - MgO (fume), March, 1989, pp. 1181-1184.

Krister Forsberg and S.Z. Mansdorf, "Quick Selection Guide to Chemical Protective Clothing", Fifth Edition.

NIOSH Occupational Health Guide for chemical Substances - Vol. II, September, 1978.

REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006.

RTECS, June 1998.

Sax - 8th Ed. TSCA Chemical Substance Inventory. Accessed at

<http://www.epa.gov/oppt/existingchemicals/pubs/tscainventory/howto.html>.

US National Library of Medicine National Institutes of Health Haz-Map. Accessed at <http://hazmap.nlm.nih.gov>

Other information : None.

Abbreviations and acronyms:

ACGIH (American Conference of Government Industrial Hygienists)

ATE: Acute Toxicity Estimate

CAS (Chemical Abstracts Service) number

EC50: Environmental Concentration associated with a response by 50% of the test population.

GHS: Globally Harmonized System (of Classification and Labeling of Chemicals)

LD50: Lethal Dose for 50% of the test population

OSHA: Occupational Safety & Health Administration

TSCA: Toxic Substances Control Act

TWA: Time Weighted Average

NFPA health hazard


: 0 - Materials that, under emergency conditions, would offer no hazard beyond that of ordinary combustible materials.

NFPA fire hazard

: 0 - Materials that will not burn under typical fire conditions, including intrinsically noncombustible materials such as concrete, stone, and sand.

NFPA reactivity

: 0 - Material that in themselves are normally stable, even under fire conditions.



Indication of changes:

Section	Changed item	Change	Comments
15	California Proposition 65 Disclosure	Added	

FloMag[®] PWT (Potable Water Treatment) Magnesium Oxide

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SDS Prepared by: The Redstone Group
6077 Frantz Rd.
Suite 206
Dublin, Ohio, USA 43017
614.923.7472
www.redstonegrp.com

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.